

Zebra® card-printer positioning guide



Model	P100i™	ZXP Series 3™	P330i™	P330m™	P430i™	ZXP Series 7™	ZXP Series 8™
Quick facts							
Product description	Single-sided single-feed colour printer	Single- or double-sided colour printer	Single-sided colour printer	Single-sided monochrome printer	Double-sided colour printer	Single- or double-sided colour printer	Single- or double-sided colour printer
Printing	Colour dye-sublimation, monochrome thermal-transfer	Colour dye-sublimation, monochrome thermal-transfer	Colour dye-sublimation, monochrome thermal-transfer	Monochrome thermal-transfer	Colour dye-sublimation, monochrome thermal-transfer	Colour dye-sublimation, monochrome thermal-transfer	Thermal-transfer and dye-diffusion to retransfer film
Printer features							
Communications interface	USB, Ethernet (opt.)	USB, Ethernet (opt.)	USB, Ethernet (opt.)	USB, Ethernet (opt.)	USB, Ethernet (opt.)	USB, Ethernet (std.)	USB, Ethernet (std.) 802.11 wireless (opt.)
Printing specifications							
Print speed	35 seconds per card colour; 6 seconds per card monochrome	180 cards per hour single-sided colour; 140 cards per hour double-sided colour; 700 cards per hour single-sided monochrome	144 cards per hour colour, 692 cards per hour monochrome	692 cards per hour monochrome	130 cards per hour single-sided colour, 102 cards per hour double-sided colour, 286 cards per hour single-sided monochrome	300 cards per hour single-sided colour, 225 cards per hour double-sided colour, 1,375 cards per hour single-sided monochrome	190 cards per hour single-sided colour, 180 cards per hour double-sided colour
Edge-to-edge printing	✓	✓	✓	✓	✓	✓	Over-the-edge
Encoder specifications							
UHF Gen 2 RFID	✗	✗	✓	✗	✓	✗	✗
Three-track magnetic	✓	✓	✓	✓	✓	✓	✓
Smart-card contact	✓	✓	✓	✓	✓	✓	✓
MIFARE® contactless	✓	✓	✓	✓	✓	✓	✓
Smart-card contact station	✗	✓	✓	✓	✓	✓	✓
Card specifications							
Card thicknesses	0.508–1.016mm (20–40 mil)	0.762mm (30 mil)	0.254–1.524mm (10–60 mil)	0.254–1.524mm (10–60 mil)	0.254–1.524mm (10–60 mil)	0.254–1.27mm (10–50 mil), 0.762mm (30 mil) laminated	0.762–1.016mm (30–40 mil), 0.762mm (30 mil) laminated
Input feeder capacity (card thickness 0.762mm/30 mil)	single card feed	100 cards	100 cards	100 cards	100 cards	200 cards	150 cards
Output hopper capacity (card thickness 0.762mm/30 mil)	–	50 cards	100 cards	100 cards	100 cards	100 cards	100 cards
Laminator specifications							
Built-in single-system laminator	✗	✗	✗	✗	✗	✓	✓

Use genuine Zebra supplies for the highest reliability and consistency in card printing

Number of images per ribbon roll/cartridge		
Model	Monochrome	Colour YMCKO
P100i	1,000	200
ZXP Series 3	1,000	200
P330i	1,500	200 & 330
P330m	1,500	–
P430i	1,500	200 & 330
ZXP Series 7	2,500 & 5,000	250 & 750
ZXP Series 8	2,500	625



Zebra supplies make it easier than ever to manage your printer

Genuine Zebra supplies meet stringent quality standards, and are recommended for optimal printing quality and proper printer performance. The ZXP Series™ printers are designed to work only with Zebra True Colours® ribbons and Zebra True Secure™ laminates and retransfer film.



For more information, visit www.zebra.com/supplies

©2013 ZIH Corp. i Series, ix Series, True Secure, and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head and True Colours are registered trademarks of ZIH Corp. All rights reserved. MIFARE is a registered trademark of Philips Semiconductors Gratkorn GmbH Ltd. All other trademarks are the property of their respective owners.



SEE MORE.
DO MORE.

www.zebra.com

Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 **Fax:** +44 (0)1628 556001 **Email:** mseurope@zebra.com **Web:** www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Russia, Spain, Sweden, Turkey

Middle East & Africa: Dubai, South Africa