



REAL-TIME DATA CAPTURE

Capture bar codes while exploiting both 1D laser and 2D imaging technologies with Standard and Extra Long Range versions available. A full VGA display and a 3.1 Megapixel color camera are featured in all WEHH Operating System configurations.

Communicate over a Laird/Summit 802.11 a/b/g/n radio with CCX v4 certification for security and seamless roaming, or through wired standards including USB Hi-Speed, RS-232, Modem and Ethernet.

Powerful parallel computer architecture combines PXA310 806 MHz and Cortex-M3 processors, increased Flash memory up to 1 GB, and a choice of Microsoft® Windows® operating systems.

ERGONOMIC & RUGGED

Users feel the full-shift difference of ergonomic handheld and pistol grip form factors to balance a 3.5 inch crystal clear display, full numeric or alphanumeric back-lit keyboards, and a one-piece 5,200 mAh battery.

Rubberized polycarbonate enclosures and a Corning® Gorilla® Glass 3 scan exit window survive daily abuse and trauma from drops to concrete. An IP65 sealing rating ensures ultimate protection against exposure to water and dust.

EASY & INTUITIVE

Develop custom solutions using the industry leading Datalogic Software Development Kit (SDK).

Deploy quickly with Datalogic Utilities, Wavelink® Avalanche® and Wavelink Scan to Configure.

Manage your installed devices using the pre-licensed Wavelink Avalanche, or leverage the included Wavelink Terminal Emulation for your legacy connectivity.



FEATURES

- Full-shift battery and a choice of 3.5 inch touchscreen displays: QVGA or VGA
- Ruggedized with 1.8 m / 6.0 ft drop to concrete resistance and IP65 sealing rating
- Standard range 1D laser and 2D imager feature Datalogic's patented 'Green Spot' technology for good-read feedback
- Auto-Ranging Laser and Extra Long Range 2D Imager
- Corning Gorilla Glass 3 scan window
- 3.1 Megapixel auto-focus camera on all WEHH models
- CCX v4 certified 802.11 a/b/g/n radio
- Windows Embedded Handheld 6.5 or Windows CE 6.0 Professional operating system
- Parallel processor architecture combines an XScale™ PXA310 806 MHz and a Cortex-M3 processor
- 256 MB RAM / 1 GB Flash memory
- Wavelink Avalanche device management and Terminal Emulation pre-licensed
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- Warehouse and Distribution Centers: Retail, Wholesale, Manufacturing, Automotive/Industrial, Electronics, Food/Beverage, Consumer Products, Pharmaceutical, Third Party Logistics (3PL)
 - Receiving
 - Cross Docking
 - Put Away
 - Staging
 - Voice Picking
 - Shipping
 - Cycle Count
 - Inventory
 - Shelf Replenishment
 - Price Management
 - Order Entry
 - Assisted Sales
 - Planogram Verification
 - Damaged Goods Documentation

TECHNICAL SPECIFICATIONS

WIRELESS COMMUNICATIONS

| | |
|-----------------------------|---|
| LOCAL AREA NETWORK (LAN) | Laird/Summit IEEE 802.11 a/b/g/n Frequency range: Country dependent, typically 2.4 GHz and 5.2 GHz; Cisco Compatible CCX v4 Security |
| PERSONAL AREA NETWORK (PAN) | Bluetooth® Wireless Technology IEEE 802.15 Class 2.1 with EDR |

DECODING CAPABILITY

| | |
|-------------------|--|
| 1D / LINEAR CODES | Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. |
| 2D CODES | Aztec Code, Data Matrix, MaxiCode, Micro QR Code, QR Code |
| POSTAL CODES | Australian Post, Intelligent Mail, Japan Post, KIX Post; Planet Code, Postnet; Royal Mail Code (RM4SCC) |
| STACKED CODES | GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, MicroPDF417, PDF417, UPC A/E Composites |

ELECTRICAL

| | |
|---------|---|
| BATTERY | Removable battery pack with rechargeable Li-ion batteries; 3.7 V 5200 mAh (19.2 Watt hours) |
|---------|---|

ENVIRONMENTAL

| | |
|---|---|
| DROP RESISTANCE | Withstands drops from 1.8 m / 6.0 ft onto concrete and 1500 random drops from 1.0 m / 3.3 ft according to IEC68-2-32 (Method 2) |
| PARTICULATE AND WATER SEALING TEMPERATURE | IP65 Operating: -20 to 50 °C / -4 to 122 °F Storage: -30 to 70 °C / -22 to 158 °F |

INTERFACES

| | |
|------------|--|
| INTERFACES | Main connector with USB 1.1 Host, USB 2.0 Hi-Speed Client, RS-232 up to 115.2 Kbps Ethernet: via single-slot dock (external module) |
|------------|--|

PHYSICAL CHARACTERISTICS

| | |
|------------------|---|
| AUDIO DIMENSIONS | Integrated microphone, high-volume speaker Handheld: 22.5 x 8.8 x 5.5 cm / 8.9 x 3.5 x 2.2 in; 6.4 x 4.0 cm / 2.5 x 1.6 in at keyboard Pistol grip: 22.5 x 8.8 x 16.8 cm / 8.9 x 3.5 x 6.6 in |
| DISPLAY | Reflective TFT daylight readable color display, 320 x 240 pixels (CE only) or 640 x 480 (WEHH only), 8.9 cm / 3.5 in diagonal, 65K colors, backlight, touch screen |
| KEYBOARD | Polycarbonate hard cap keyboards with backlight; 29-key numeric or 52-key alphanumeric with discrete navigation |
| WEIGHT | Handheld: 608.0 g / 21.4 oz Pistol grip: 674.0 g / 23.8 oz |

SAFETY AND REGULATORY

| | |
|--------------------------|---|
| AGENCY APPROVALS | The product meets necessary safety and regulatory approvals for its intended use. The Users Manual for this product can be referred to for a complete list of certifications. |
| ENVIRONMENTAL COMPLIANCE | Complies to EU RoHS |
| LASER CLASSIFICATION | VLD - Class 2 IEC/EN60825-10. Compliant with 21 CFR 1040.10 except for deviations pursuant to laser notice Number 50, dated June 24, 2007 |
| LED CLASSIFICATION | Exempt Risk Group IEC/EN62471 |

READING PERFORMANCE

| | |
|----------------------------------|--|
| HIGH PERFORMANCE LASER (HPL) | Depth of Field: 1 to 83 cm / 1 to 32 in, depending on bar code and density; Scanning Rate: 104 +/- 12 scans/sec.; Good Read Feedback: Datalogic's patented 'Green Spot' technology |
| LONG-RANGE LASER (XLR) | Depth of Field: Non-reflective labels from 9 to 490 cm / 0.3 to 16.0 ft, depending on bar code density; Reflective labels: up to 1509 cm / 49.5 ft. Near range determined by degree of reflectivity and width of the bar code. All ranges dependent on bar code size and density; Scanning Rate: 31-41 scans/sec. Minimum Resolution: 0.20 mm / 7.5 mils |
| STANDARD RANGE IMAGER (2D) | Depth of Field: 2 to 60 cm / 1 to 24 in, depending on bar code size and density; Minimum Resolution: Linear codes: 5 mils; 2D codes: 6.7 mils; Good Read Feedback: Datalogic's patented 'Green Spot' technology |
| EXTRA LONG RANGE IMAGER (2D XLR) | Depth of Field: 17 to 952 cm / 0.6 to 31.3 ft, depending on bar code size and density; Minimum Resolution: Linear codes: 5 mils; 2D codes: 10 mils |
| SCAN WINDOW | All scan engines feature Corning® Gorilla® Glass 3 window |
| CAMERA | 3.1 Megapixel color with auto-focus and LED flash (WEHH only); Image Formats: BMP, JPEG |

SOFTWARE

| | |
|---------------------------------|--|
| CONFIGURATION & MAINTENANCE | Wavelink Avalanche pre-licensed, Avalanche Remote Control™, Datalogic Firmware Utility (DFU), Datalogic Desktop Utility (DDU), Datalogic Configuration Utility (DCU) |
| DEVELOPMENT | Windows SDK, Datalogic SDK (C/C++, .NET, Java); Wavelink Studio®; MCL-Collection™; Java Virtual Machine |
| APPLICATIONS TERMINAL EMULATION | Pal Application Library pre-licensed Wavelink Terminal Emulation pre-licensed, Wavelink Industrial Browser™ |
| SECURITY | Wavelink SecurePlus; Wavelink Certificate Manager |
| VOICE-PICKING | Vo-CE™; Wavelink Speakeasy™ |

SYSTEM

| | |
|------------------|---|
| OPERATING SYSTEM | Microsoft Windows CE 6.0 Professional with Microsoft WordPad and Internet Explorer® 6.0; Windows Embedded Handheld 6.5 with Office Mobile; Outlook® Mobile, Word Mobile, Excel® Mobile, PowerPoint® Mobile, OneNote® Mobile and Internet Explorer® Mobile 6.0 |
| MICROPROCESSOR | XScale™ PXA310 @ 806 MHz |
| COPROCESSOR | Cortex-M3, 32 bit |
| MEMORY | System RAM: 256 MB, System Flash: 1 GB |
| EXPANSION SLOTS | MicroSD card slot compatible with microSD-HC cards, user-accessible |
| REAL-TIME CLOCK | Time and date stamping under software control |

WARRANTY

| | |
|----------|-------------------------|
| WARRANTY | 1-Year Factory Warranty |
|----------|-------------------------|



Caution: Laser Radiation - do not stare into beam

ACCESSORIES

Docks



- 94A150057 Single Slot Dock w/Spare Battery Charging Slot



- 94A150056 Multi-Ethernet Dock Charges 4 terminals and 4 Batteries



- 94A151131 Vehicle Dock

Battery Chargers



- 94A151137 Multi Battery Charger



- 94A151135 Multi Charge Only Dock Charges 4 terminals and 4 Batteries

Cases/Holsters



- 94ACC0104 Rubber Boot



- 94ACC0047 Standard Softcase with Quick Release Belt Clip