

# CODE READER™ 1000



Compact, efficient and powerful, this is advanced technology at a maximum value.

Weighing in at just 2.4 oz, capable of withstanding multiple drops from 6 feet and able to work at 131° F, the simple and intuitive CR1000 could be the toughest featherweight you'll ever meet. It quickly and reliably decodes 1D, 2D and Postal barcodes from any surface type. Featuring Code's Affinity<sup>®</sup> rapid disconnect cable set, you can count on durable connectivity between reader and host device, with the ability to quickly remove and replace damaged cables. For data editing and parsing, end users can leverage its JavaScript platform to create custom routines and applications that are easily embedded into the reader.

## Features & Benefits

- High speed, omnidirectional reading of 1D, 2D and Postal barcodes
- Manual or automatic triggering
- Bright LED indicator and loud, programmable tone indicator
- Reads barcodes on mobile devices
- Compatible with Code's CortexTools<sup>®</sup> software configuration utility
- Data editing and parsing with JavaScript
- Uses Code's rapid disconnect Affinity<sup>®</sup> cables
- Extremely efficient power consumption (lowest in its class)
- Optional stand
- Disinfectant-ready IP54 housing
- Available in light and dark gray

## Advanced data management and excellent versatility.

In retail applications, the CR1000 excels in and can be combined with various peripherals for a truly unique point-of-sale solution. From mobile devices like workstations-on-wheels, tablet PCs or environmentally conscious kiosk operators, the CR1000 works on a large scale in a limited workspace.

For intuitive, lightning fast performance that won't drain your battery or your budget, choose the CR1000.

## Applications

Healthcare, mobile coupon and ticketing, pharmacy, patrol vehicles, ATMs and kiosks, retail, and manufacturing

## Features at a Glance



# CODE READER™ 1000 SPECIFICATIONS

## Physical Characteristics

<b>CR1000 Dimensions</b>	1.18" H x 2.6" L x 2.2" W (30 mm H x 67 mm L x 52 mm W)
<b>CR1000 Weight</b>	2.4 oz (68 g)
<b>Color Options</b>	Available in light or dark gray
<b>IP Rating</b>	54

## User Environment

<b>Operating Temperature</b>	-20° to 55° C / -4° to 131° F
<b>Storage Temperature</b>	-30° to 65° C / -22° to 150° F
<b>Humidity</b>	5% to 95% non-condensing
<b>Decode Capability</b>	<p><b>1D:</b> Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, IATA 2 of 5, Interleaved 2 of 5, GS1 DataBar (RSS), Hong Kong 2 of 5, Matrix 2 of 5, MSI Plessey, NEC 2 of 5, Pharmacode, Plessey, Straight 2 of 5, Telepen, Trioptic, UPC/EAN/JAN</p> <p><b>Stacked 1D:</b> GS1 Composite (CC-A/CC-B/CC-C), MicroPDF, PDF417</p> <p><b>2D:</b> Aztec Code, Code 49, Codablock F, Data Matrix, Han Xin, MaxiCode, Micro QR, QR Code</p> <p><b>Proprietary 2D:</b> GoCode® (Additional License Required)</p> <p><b>Postal Codes:</b> Australian Post, Intelligent Mail, Japan Post, KIX Code, Korea Post, Planet, Postnet, UK Royal Mail, UPU ID-tags</p>
<b>Image Output Options</b>	Formats: JPEG or PGM
<b>Field Selection</b>	High Density or Wide Field
<b>Data Editing</b>	JavaScript

## Working Ranges

### CR1000 Performance

Test Barcode	Min Inches (mm)	Max Inches (mm)
3 mil Code 39	3.1" (80 mm)	4.0" (102 mm)
7.5 mil Code 39	1.3" (33 mm)	7.2" (182 mm)
10.5 mil GS1 DataBar	0.8" (20 mm)	8.7" (220 mm)
13 mil UPC	1.1" (28 mm)	11.0" (280 mm)
5 mil DM	1.7" (43 mm)	4.5" (115 mm)
6.3 mil DM	1.3" (33 mm)	5.9" (150 mm)
10 mil DM	0.8" (20 mm)	7.1" (180 mm)
20.8 mil DM	1.1" (28 mm)	13.5" (343 mm)

Note: Working ranges are a combination of both the wide and high density fields. All samples were high quality barcodes and were read along a physical center line at a 10° angle. Default AGC settings were used. Accuracy= +/- 10%.

## Performance Characteristics

<b>Field of View</b>	High Density Field: 30° horizontal by 20° vertical Wide Field: 50° horizontal by 33.5° vertical
<b>Focal Point</b>	High Density Field: approximately 100 mm Wide Field: approximately 115 mm
<b>Sensor</b>	CMOS 1.2 Megapixel (1280 x 960) gray scale
<b>Optical Resolution</b>	High Density Field: 960 x 640 Wide Field: 960 x 640
<b>Pitch</b>	± 60° (from front to back)
<b>Skew</b>	± 60° from plane parallel to symbol (side-to-side)
<b>Rotational Tolerance</b>	± 180°
<b>Print Contrast</b>	25% absolute dark/light reflectance differential, measured at 650 nm
<b>Target Beam</b>	Single, blue targeting bar
<b>Ambient Light Immunity</b>	Sunlight: Up to 9,000ft-candles/96,890 lux
<b>Shock</b>	Withstands multiple drops of 6' (1.8 Meters to concrete)
<b>Power Requirements</b>	Reader @ 5vdc (mA): Typical = less than 450 mA; Idle = less than 80 mA; Sleep = less than 31 mA
<b>Memory Capacity</b>	128MB Flash ROM, 32MB RAM
<b>Communication Interfaces</b>	RS232, USB 2.0 (Generic HID, HID Keyboard, Virtual COM Port)
<b>Warranty*</b>	2 years

## Accessories

- Various cable options available. Visit [www.codecorp.com/cables.php](http://www.codecorp.com/cables.php) for a list of compatible cables



- Stand

**code**®  
ADVANCED BARCODE READERS

Web: [www.codecorp.com](http://www.codecorp.com)

\* Warranty period is specific to North America and EMEA.

