

	<b>Zebra ET50/55</b>	<b>GETAC Z710</b>	<b>GETAC T800</b>	<b>CASIO VT500-GE</b>
Tipus	Ipari Enterprise Tablet	Ipari Android tablet	Ipari Windows tablet	Robusztus Android tablet
OS	Windows Embedded Industry Pro 8.1 (Windows 10-ready) OR Android 5.1	Android 4.1	Windows 8.1 Professional	Android 4.0.4
Processor	Quad-core Intel (est: Bay Trail J1900 (Windows) and E3845 (Android))	Dual core TI OMAP 4430	Quad-core "Bay Trail" Intel N3530 w/ 2MB cache	OMAP4460
CPU Speed	Max 2.4GHz and 1.9GHz	1GHz	2.16 GHz (2.58 GHz Turbo Boost)	1,5 GHz
Standard/Max RAM	4GB LPDDR3 (Windows), 2GB LPDDR3 (Android)	1GB MDDR	4GB DDR3L	1GB
Disk/drive	64GB eMMC Flash (Windows), 32GB eMMC Flash (Android), microSDXC	16GB iNAND Flash	SATA SSD 64GB	16GB
Kártya helyek	1 microSDXC (up to 2TB)	1 microSD (up to 32GB), 1 SIM card	Factory installed options: either 1D/2D barcode reader or gigabit R145 LAN	SD kártya (SDHC / microSDHC / SAM slot
Képernyő	TFT with Corning Gorilla Glass 3	TFT LCD Gorilla Glass	Sunlight-readable "LumiBond" kijelző. 600 nits	IPS TFT színes LED háttérvilágítással
Képernyő mérete	8.3" (440 NIT) and 10.1" (350 NIT), 1920 x 1200 pixel (16:10 aspect ratio)	7.0-inch/1024 x 600 pixel WVGA	8.1-inch/1280 x 800 pixel	10,1-inch/1280 x 800 pixel
Digitizer/pens	Capacitive 10-point multi-touch, active digitizer pen	Capacitive touch (usable with gloves and stylus)	Capacitive multi-touch	Capacitive multi-touch
Billentyűzet	Onscreen keyboard + optional external	Optional external	Optional external	Onscreen keyboard
Működési tartomány	0° to 50°C	-20°C to +50°C	-21°C to +50°C	-20°C to +50°C
IP védelem	IP65	IP65	IP65	IP54
Shock	3-foot drops per MIL-STD-810G (6-foot with optional rugged frame)	26 drops from 6-foot	26 drops from 6-foot	
Vibráció	Operational: random vibration 10-1000 Hz 1.9g RMS, 1 hour duration per axis			
Méretetek (WxHxD)	228 x 150 x 12.5mm 10.1" tablet: 269 x 181 x 12.5mm	219 x 143 x 28 mm	227 x 151 x 24 mm	269 x 14,4 x 190 mm
Súly	8.3" tablet: 555 gramm 10.1" tablet: 750 gramm	815 gramm	950 gramm	780 gramm
Akkumulátor	8.3" tablet: 5,900 mAh Li-Ion, 10.1" tablet: 8,700 mAh Li-Ion, optional 6.800 mAh secondary battery	7,600mAh Li-Ion 10 órás működéssel	2,100mAh Li-Ion 8 órás működéssel	Lithium-polymer 12 órás működéssel
Szenzorok	3-axis motion, gyroscope, ambient light, e-Compass	e-compass, g-sensor	-	-
Kamera	Hátsó: 8mp auto-focus, LED-es vakuval (támogatja az 1D/2D vonalkódolvasást, video készítést); első: 2mp 1080p (1920 x 1080 pixel) 30fps video	1 első (HD), 1 hátsó (5mp AF)	Első: HD webcam , hátsó 5mp	Első: 5mp, Hátsó 5mp AF
Interface	Docking connector (USB 3.0, HDMI, charging); rugged connector for use with rugged dock (1 x USB 2.0, 1 x 3.5mm audio jack, microUSB (for charging)	1 USB 2.0, 1 micro-USB, microphone, 2 external antenna, dock	1 x USB 3.0, 1 x Micro HDMI, audio in/out, dock; optional via SnapBack modules: SmartCard & RFID, SmartCard & magstripe	USB2.0 Type A / USB2.0 Mini- B
Kommunikáció	Dual-band 802.11a/b/g/n/k/r WiFi, Class 2 Bluetooth v4.0, autonomous GPS; ET55 model has global LTE with HSPA+ (North America multi-carrier LTE with both Verizon (EVDO) and AT&T (HSPA+) 3G fallback)	WiFi, Bluetooth; optional 3G WWAN, GPS (SiRFstar IV), RFID, HD webcam, 5mp camera, 1D laser or 1D/2D CMOS imager; optional mag stripe and smart card reader	802.11ac WiFi + Bluetooth; dedicated GPS; optional 4G LTE WWAN, SnapBack SmartCard reader, RFID, mag stripe reader	802.11a/b/g/n WiFi, Class 2 Bluetooth v4.0, GPS, HSPA/UMTS/EGPRS/EDGE/GP RS, NFC
List price				